



Torque wrench with dial gauge display, maximum torque: 280N·m



Order data

| | |
|--------------|---------------|
| Order number | 655520 280 |
| GTIN | 4045197549969 |
| Item class | 62E |

Description

Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: Nm Non-slip 2-component handle.

Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: $\pm 4\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 690 mm

Torque range: 56 - 280 N·m

Scale graduation, 1 graduation =: 5 N·m

Weight: 1650 g

Square drive: 1/2 in

Technical description

| | |
|----------------|---------|
| maximum torque | 280 N·m |
|----------------|---------|

| | |
|--|-------------------------------------|
| Square drive | 1/2 in |
| Weight | 1650 g |
| Display | analogue |
| Torque measuring accuracy | ±4 % |
| Direction of tightening | For right and left-hand tightening |
| Scale graduation, 1 graduation = | 5 N·m |
| Torque range | 56 - 280 N·m |
| Lever length without plug-in head [L ₁] | 535 mm |
| Lever length including factory calibration reference dimension [L ₃] | 605 mm |
| Setting the trigger value | Memory pointer |
| Connection format | Push-through square drive (ratchet) |
| Measurement process | Torque |
| Overall length L | 690 mm |
| Adjustable trigger value | non-adjustable |
| Feedback | displaying |
| Reversible reading | Nm |
| Standard | DIN EN ISO 6789 |
| Calibration | O3 |
| Test certificate | Manufacturer's test certificate |
| Data can be recorded | no |
| Release signalling | visual |
| Measurement technology | mechanical |
| Type of product | Torque Wrench |

Services

| | |
|--|---------------|
| Calibration Torque wrench both ends maximum torque 400/2 N·m | 018821 400/2 |
| Labelling laser-etched Type | 018940 |
| | 018831 1000/2 |

| | |
|---|---------------|
| DAkKS calibration Torque wrench both ends maximum torque 1000/2 N·m | |
| DAkKS calibration Torque wrench both ends maximum torque 1000/2 N·m | 020040 1000/2 |
| Calibration Torque wrench both ends maximum torque 400/2 N·m | 020030 400/2 |