

Garant**Stepladder, double-sided access, Number of steps: 2X4****Order data**

Order number	965920 2X4
GTIN	4045197742087
Item class	91B

Description**Version:**

Aluminium stepladder, permanent connection between steps and stiles, flanged on all 4 sides. 80 mm deep treads with non-slip serrated surfaces. Great stability due to robust construction. Solid aluminium ladder joint with 4 screw connections. EasyHandle Haptoprene® handle with clamping mechanism, non-slip BalanceBase end caps. With 2 high-strength Perlon straps to prevent splay. With SafeStep marking to identify the highest access step.

Standard:

Gemäß DIN EN 131-2, BetrSichV, TRBS 2121, DGUV Information 208-016 bzw. 208-017 und geltendem DGUV Regelwerk.

Colour:

Stiles anthracite RAL 7016 **powder-coated**.
Hoffmann perforated panel grid interval: 9×9
Length L: 0.93 m
Ladder length: 0.93 m
Working height approx.: 2.5 m
outer width at bottom: 0.46 m
Cross beam width: 73 mm
Weight: 6.7 kg

Technical description

Ladder length	0.93 m
Accessibility	double-sided
Weight	6.7 kg
Working height approx.	2.5 m
outer width at bottom	0.46 m
Cross beam width	73 mm
Length L	0.93 m
Ladders and platforms load capacity	150 kg
Hoffmann perforated panel grid interval	9×9
Type of product	Stepladder