

ESD plug-in extension rack, Depth 400 mm, Height: 2000mm



Order data

Order number	972505 2000
GTIN	4062406180751
Item class	911

Description

Version:

Sturdy column frame of rectangular columns ($50 \times 25 \times 1.25$ mm) with slots at intervals of 40 mm for mounting cross beams / shelves. Column frames with non-conductive plastic end caps. No tools required for assembly. The high lateral stability eliminates the need for diagonal struts for stabilisation. Storage shelves are **ESD powder-coated**. A galvanised spring on the storage shelf ensure reliable contact with the installed earthing point.

Supplied with:

Includes ESD grounding cable.

Colour:

Light grey similar to RAL 7035 ESD powder-coated.

Note:

- To ensure the stability of the racking, measures to prevent tipping are necessary where the height to depth ratio is greater than 5:1.
- · All plastic components (e.g. covering caps) are not ESD conductive.

electrical insulation: EGB/ESD

Assembled size basic rack width: 975 mm

Shelf width: 946 mm

Storage shelf clear width: 900 mm

Number of shelves: 4 maximum bay load: 900 kg



Technical description

Storage shelf clear width	900 mm
Shelf width	946 mm
maximum bay load	900 kg
Assembled size basic rack width	975 mm
Number of shelves	4
Shelf load capacity / maximum distributed shelf load (on metal)	120 kg
Shelf thickness	38 mm
Height adjustment interval	40 mm
electrostatic characteristic	EGB/ESD
Product name attribute	Depth 400 mm
Type of product	Storage shelf