



## Safety cabinet Q-Pegasus type 90, Width: 600 mm



### Order data

Order number	981015 600
GTIN	2050001709790
Item class	96G

### Description

#### NOTE: Colour selection possible

#### Version:

Cabinet casing of sheet metal with integral door position detector, interior with chemically resistant surface.

- **Mountings for shelves at 32 mm intervals.**
- **Floor-level containment tray (satisfies StawaR).**
- **With exhaust air connection (NB 75).**
- **Including door position detector.**
- **Lockable with profile half-cylinder, can be integrated into the company's locking system. Not compatible with the Hoffmann locking system.**
- **With 4 height adjustment feet to compensate for unevenness in the floor.**

With **AGT** (Asynchronously Linked Door Drive), **TSA** (Automatic Door Closer) with visual and acoustic warning of automatic door closing. 1-door

#### Application:

Secure storage in accordance with regulations of flammable hazardous substances in work areas.

#### Standard:

DIN EN 14470-1, Typgeprüft (Brandkammergetestet), **90 Minuten feuerbeständig (nach höchster Brandschutzstufe der TRGS 510 Anlage 3).**

#### Supplied with:

Cabinet with 3 storage shelves, perforated panel insert and floor-level drip tray, plastic-coated and base fascia, 1 service log book.

**Colour:**

Cabinet casing RAL 7016 anthracite grey, doors **signal blue RAL 5005**.

**Note:**

At regular intervals (annually), safety cabinets should be maintained and their operating characteristics checked by an authorised competent person.

Fire resistance: 90 min

Height: 1953 mm

Width: 599 mm

Depth: 615 mm

Usable height: 1647 mm

Usable width: 450 mm

Usable depth: 522 mm

## Technical description

Usable width	450 mm
Usable height	1647 mm
Number of floor-level containment trays	1
Number of shelves	3
Width	599 mm
Number of perforated plate inserts	1
Volume of floor-level drip tray	22 l
Depth	615 mm
Usable depth	522 mm
Height	1953 mm
Load capacity of shelf	75 kg
Weight	283 kg
Height adjustment interval	32 mm
Colour selection	Body – RAL 7016, fronts – RAL 7035, 1004, 3020, 5010, 5005, ...
Fire resistance	90 min
Type of product	Safety cabinet

