

**Garant**
**GARANT Master Alu PickPocket solid carbide roughing end mill HPC, DLC, Ø e6 DC: 10mm**

**Order data**

Order number	202017 10
GTIN	4062406381042
Item class	11X

**Description**
**Version:**

For roughing and finishing.

Up to 2×D into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to 45°.

Very long overhang for safe machining of deep cavities.

With the latest generation of DLC coating sp<sup>2</sup>.

**Advantage:**

**Optimised flute form, eccentric relief ground, generous chip spaces.**

**Note:**

A minimum oversize of 0.1×D must be maintained for subsequent finishing operations.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 42°

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L<sub>c</sub>: 16 mm

Overhang length L<sub>1</sub> incl. recess: 58 mm

Recess Ø D<sub>1</sub>: 9.2 mm

Overall length L: 100 mm

Shank Ø D<sub>s</sub>: 10 mm

**Technical description**

Overall length L	100 mm
Overhang length L <sub>1</sub> incl. recess	58 mm
Helix angle	42°
No. of teeth Z	3
Shank Ø D <sub>s</sub>	10 mm
Feed f <sub>z</sub> for slot milling in short-chipping aluminium	0.05 mm
Shank	DIN 6535 HA to h6
Feed f <sub>z</sub> for side milling in short-chipping aluminium	0.07 mm
Recess Ø D <sub>1</sub>	9.2 mm
Balance quality with shank	G 2.5 with HA
Cutting edge Ø D <sub>c</sub>	10 mm
Tolerance nominal Ø	e8
Flute length L <sub>c</sub>	16 mm
Direction of infeed	horizontal, oblique and vertical
Corner rounding r <sub>v</sub>	0.2 mm
Series	Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a <sub>e</sub> for milling operation	0.3×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End / face mill

## User data

	<b>Suitability</b>	<b>V<sub>c</sub></b>	<b>ISO code</b>
Aluminium	Suitable	380 m/min	N
Aluminium (short chipping)	suitable	300 m/min	N
Alu > 10% Si	Suitable	270 m/min	N
PMMA acrylic	Suitable	180 m/min	N
PE-HD	Suitable	130 m/min	N
PA 66	Suitable	150 m/min	N
PEEK	Suitable	130 m/min	N
PF 31	Suitable	110 m/min	N
PVDF GF20	Suitable	160 m/min	N
POM GF25	Suitable	150 m/min	N
PA 66 GF30	Suitable	140 m/min	N
PEEK GF30	Suitable	120 m/min	N
PTFE CF25	Suitable	150 m/min	N
Honeycomb sandwich	suitable only under restricted conditions	220 m/min	N
Cu	Suitable	140 m/min	N
CuZn	Suitable	160 m/min	N
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable only under restricted conditions		
Air	suitable		