

Synchro tool head for ER32, Tap shank Ø d2: 7mm



Order data

Order number	338186 7
GTIN	4062406103644
Item class	31P

Description

Version:

- · Tapping and thread forming on machines with synchronised spindles.
- Minimum Length Adjustment: +0.5mm / -0.2 mm.
- · Compensation for synchronisation errors, hence better thread quality and clear increase in tool life.
- · For collet chucks and driven tools to ISO 15488 (DIN 6499).
- Suitable for left-hand and right-hand threads.

Standard:

- · Minimum Length Adjustment: +0.5mm / -0.2 mm.
- · Compensation for synchronisation errors, hence better thread quality and clear increase in tool life.

Suitable for:

ER synchro collet No. 338180.

Through-coolant: yes, with max. 50 bar

Ø D₂: 25 mm

for tap shank \emptyset d₂ DIN 371: M7

for tap shank Ø d₂ DIN 374/376: M9-10

Overhang L₁: 19 mm Shank square: 5.5 mm

Technical description

Overhang L ₁	19 mm
Shank square	5.5 mm

for tap shank \emptyset d ₂ DIN 371	M7
for tap shank \emptyset d ₂ DIN 374/376	M9-10
$ØD_2$	25 mm
Through-coolant	yes, with max. 50 bar
Type of product	Tapping adapter